


SPECIFICATION:

- 1). Driving: Duty: 1/240, Bias: 1/16, VDD: 5.0V, VO: 22.0V(Ref.)
- 2). VIEWING DIRECTION: 6 O'CLOCK
- 3). Display mode: STN/Negative/Transmissive/Blue
- 4). Operating temp.: -20°C~+70°C
- 5). Storage temp.: -30°C~+80°C
- 6). USE IC: NT7701/NT7702
- 7). Backlight: EDGE/CCFL White
- 8). DIMENSIONS WITH MARK "*" ARE IMPORTANT WITH MARK "()" ARE REFERENCED
- 9). All the raw materials are RoHS compliant



REV	REVISION RECORD	DATE	1	2	3	4	5	6	7	8	9	10	11	12
A0	First Issue	12-10	FRM	LP	CP	NC	DISP	D0	D1	D2	D3	VDD	VSS	VO

REV	REVISION RECORD	DATE	DRAWING NO.		APPROVED BY		DRAWING BY		UNIT:	GENERAL TOL:	PAGE
A0	First Issue	12-10	SYT320191V17-59FM2-96N2F-T044.5		TCC		TCC		mm	± 0.2	1/1


深圳市三元晶科技有限公司
 ShenZhen TCC LCD Hi-Tech Co., Ltd.